

# in Touch Stretch ディスプレイ

## Interactive Smart Display

タッチパネル採用のストレッチディスプレイ



### 23インチ in Touchディスプレイ LD230EKS-FPN1

- 23.1インチフルスクリーン「in-TOUCH」ディスプレイ
- 700cdの高輝度
- Androidベースプラットフォーム
- スリム&軽量
- 画面タッチによる操作

### 29インチ in Touchディスプレイ LD290EJS-FPN1

- 29インチフルスクリーン「in-TOUCH」ディスプレイ
- 500cdの高輝度
- Androidベースプラットフォーム
- スリム&軽量
- 画面タッチによる操作







## 製品仕様

Model		LD230EKS-FPN1	LD290EJS-FPN1
ディスプレイ	Screen Size (inch)	23"	29"
	Resolution	1920 x158	1920 x 540
	Brightness	700cd/m2 (Typ.)	500cd/m2 (Typ.)
	Active Screen Size [mm]	585.6(H)×48.19(V)	698.4(H) x 196.43(V)
	Bezel (mm, L/R/U/D)	4.1/4.1/5.6/9.6	7.2/7.2/7.7/9.6
	refresh rate	60Hz	
	Product Life	50,000 Hrs	
	Panel Surface	Anti Glare, 3H	
タッチ	Touch	in TOUCH (P Cap in cell Touch)	
	Report rate	60Hz	
	Multi Touch	≤10 points	
システム	CPU	ARM®Cortex™-A17, Quad-core, 1.6MHz,	
	OS	Android 7.1	
	RMA	DDR3 1GByte	
	Memory	eMMC 8GByte	
	Power Consumption (Typ.)	<15W	<30W
	WiFi	WIFI 802.11b/g/n (2.4GHz)	
	Bluetooth	BT 4.2	
	Connectivity	Micro USB 2.0 (Host 1ea, OTG 1ea)	
	Signal Output	Micro HDMI	
	Operating Mode	Portrait / Landscape	
Audio	Audio Codec List	MPEG Audio, WAV Audio, OGG Audio, FLAC Audio, MIDI Audio	MPEG Audio, WAV Audio, OGG Audio, FLAC Audio, MIDI Audio, AAC
Video	Video Codec List (Still Image)	JPEG, BMP, GIF, PNG	
	Video Codec List (Moving Image)	MPEG-2, GOOGLE VP8, H.263, MOTION JPEG	MPEG-2, GOOGLE VP8, H.263, MOTION JPEG, MPEG-4, H.264, H.265
使用環境	Operating Temperature	0°C ~45°C	
	Operation Humidity	10~80%RH	
	Storage Temperature	-20°C ~60°C	
	Operating Time	24 / 7 Days	
電源仕様 (ACアダプター別売り)	Input Power	AC100, 240V@50/60Hz, 12V, 3A, USB Type C (Power Only)	
外形仕様	Outline Dimension (mm)	593.8 (H) x 63.4 (V) x 19.7(D)	712.8 (H) x 213.74 (V) x 16.1(D)
	Weight	0.82kg(Typ.)	2.80Kg (Typ.)